

# Warning VATCS – Dynamic Curve Series

Independently proven to reduce average approach speeds to curves by up to 11kph and significantly lower the occurrence of lane departure fatalities



Hazard specific

Independently proven to be long term effective

11kph reduction on average curve approach speed maintained after 3 years - TRL 548 report

1/3rd drop in curve accident rate after 3 years - TRL 548 report

Dynamic flashing corner beacons attract driver attention

Clear speed management strategy in line with MUTCD

Dual directional arrow diagram models available



## Proven Traffic Calming Solutions

All dynamic curve warning VATCS signs employ microwave doppler radar to detect vehicle approach speeds and in line with the core MUTCD philosophy of consistent road speed management strategy, utilize horizontal curve warning diagrams that are already recognized in the MUTCD.


The dynamic curve warning VATCS are installed in advance of the curve and downstream and in tandem with existing static warning signage so that targeted drivers are not informed what speed they are travelling, rather they are advised of the approaching hazard with request to SLOW DOWN further enhanced by dynamic flashing pairs of horizontal beacons.

The VATCS are not a replacement for static signage.

Curve Warning VATCS are available in a range of diagram sizes from 600 x 600mm to 900 x 900mm. Deploying the VATCS family sign series will provide a consistent and clear approach for managing driver speeds in your community.

VATCS are the only traffic calming display technology that has been federally field tested on a large scale to prove long term effectiveness, with driver respect of the technology being maintained over a 5 year period.

First introduced in 2008 after being piloted by various communities in Ontario, VATCS are now in operation across 5 provinces and are steadily becoming the benchmark for consistent community display based traffic calming.



## Technical Data

<b>Model Reference</b>	Warning VATCS – Dynamic Curve Series VATCS/Wa – XLR/SD/L/DL/PT
<b>Display Technology</b>	ITE color tested high intensity LED display. Optical performance in compliance with FHWA MUTCD, Auto Luminosity control to suit ambient light conditions.
<b>Display Format</b>	Color inverted MUTCD horizontal curve warning diagram, 600mm to 750mm diagram size options, complete with matching Slow Down message and amber flashing beacon pairs. Slow Down text height 100mm and 150mm to suit 600mm and 750mm model sizes. Beacons 125mm in diameter.
<b>Vehicle Detection</b>	FCC compliant K band radar microwave vehicle detector integrated into the sign, factory preset range of 600 feet / 190Metres. Speed range of 8 to 240kph. 12 degree beam accuracy +/-1 unit of measure. Simple set up.
<b>Model Dimensions</b>	600 x 600mm Size 1681mm high x 956mm wide x 150mm deep 750 x 750mm Size 1881mm high x 1156mm wide x 150mm deep
<b>Model Weights</b>	600 x 600mm Size 45Kg (plus batteries in case of solar) 750 x 750mm Size 60Kg (plus batteries in case of solar)
<b>Power Supply</b>	Display is dual Solar DC and AC 110V compatible as standard. In the case of Solar power installs SP8054 solar kits should be ordered for each sign comprising 80W panel, side of pole mount and 4 x 12V 20amp/hr battery reservoir which are mounted internal to sign. Important for 24/7/365 solar operation, solar panel must be facing due south and have clear unobstructed view of sky with no shadowing.
<b>Data Logging and Analysis Software</b>	Datalogger windows based software is available to download date and time stamped traffic speed data from sign over Bluetooth™ for evaluation analysis in Excel.
<b>Sign Configuration</b>	Custom windows based software over Bluetooth™ wireless connection from client supplied Laptop or Netbook.
<b>Enclosure</b>	Purpose fabricated lightweight vandal resistant NEMA Type 3S ingress rated enclosure.
<b>Finish</b>	Matt Black front face Aircraft Grey rear powder coat finish or color to suit, 60 micron min thickness.
<b>Window</b>	5mm anti reflective Polycarbonate.
<b>Operating Temp Range</b>	-35 to + 74°C, 95% non condensing.
<b>Mechanical Interface</b>	Sign will be supplied equipped with sign fix U channel supports on rear and SX0220 channel banding interface brackets to allow ¾" band mounting to a variety of support posts. Solar Panel equipment is supplied with side pole mount to allow ½" banding.
<b>Electrical Interface</b>	Cable kits are supplied to facilitate plug and play connection to solar panel and sign. Sign also equipped on rear with naked AC plug and socket type 6P connection and separate ¾" knock out for conduit cable entry. Dust Caps are supplied to protect any unused sockets. Internal power connections are screw terminal.



## Operation

**The VATCS sign is designed to operate in both ACTIVE and STEALTH mode.**

STEALTH mode is used to allow client to attain a baseline of road speed from the VATCS without the VATCS displaying any visual warning to the approaching traffic.

Once collected this base data can be compared against historic data and then importantly used to evaluate performance of the sign in ACTIVE mode.

Once in ACTIVE mode the sign upon detecting an approach speed above the pre-configured trigger speed will cause the warning display to be illuminated for 3.5 seconds giving drivers sufficient time to digest and adjust behaviour appropriately.

When vehicles are travelling below the trigger speed the sign will remain entirely blank, importantly the warning message is only targeted at offending vehicles. It is normal practice for curve warning sign applications to set trigger speed to 10% + 3kph above the posted speed limit or at the 50th percentile approach speed to the curve if known.

All VATCS are supplied with full operator manual which contains a guide to installation and set up best practices, which it is recommended are followed to ensure optimal performance and results.

## Dynamic Curve Series - Uniplan Product Coding

MUTCD CODE REF	LEFT TURN	DUAL DIRECTION DISPLAY	RIGHT TURN	MUTCD CODE REF
<b>Wa-1L</b>  <b>Turn</b>	Single Direction Left Curve Model: VATCS/Wa-1L/SD/L/DL/PT  Uniplan Part Number: WWWa-1L-SLDPCAP (600 x 600 Size) WWWa-1L-SLDPCBP (750 x 750 Size)	Dual Direction Curve Model: VATCS/Wa-1LR/SD/L/DL/PT  Uniplan Part Number: WWWa-1LRSLDPCAP (600 x 600 Size) WWWa-1LRSLDPCBP (750 x 750 Size)	Single Direction Right Curve Model: VATCS/Wa-1R/SD/L/DL/PT  Uniplan Part Number: WWWa-1RSLDPCAP (600 x 600 Size) WWWa-1RSLDPCBP (750 x 750 Size)	<b>Wa-1R</b>  <b>Turn</b>
<b>Wa-2L</b>  <b>Sharp Curve</b>	Single Direction Left Curve Model: VATCS/Wa-2L/SD/L/DL/PT  Uniplan Part Number: WWWa-2L-SLDPCAP (600 x 600 Size) WWWa-2L-SLDPCBP (750 x 750 Size)	Dual Direction Curve Model: VATCS/Wa-2LR/SD/L/DL/PT  Uniplan Part Number: WWWa-2LRSLDPCAP (600 x 600 Size) WWWa-2LRSLDPCBP (750 x 750 Size)	Single Direction Right Curve Model: VATCS/Wa-2R/SD/L/DL/PT  Uniplan Part Number: WWWa-2RSLDPCAP (600 x 600 Size) WWWa-2RSLDPCBP (750 x 750 Size)	<b>Wa-2R</b>  <b>Sharp Curve</b>
<b>Wa-3L</b>  <b>Curve</b>	Single Direction Left Curve Model: VATCS/Wa-3L/SD/L/DL/PT  Uniplan Part Number: WWWa-3L-SLDPCAP (600 x 600 Size) WWWa-3L-SLDPCBP (750 x 750 Size)	Dual Direction Curve Model: VATCS/Wa-3LR/SD/L/DL/PT  Uniplan Part Number: WWWa-3LRSLDPCAP (600 x 600 Size) WWWa-3LRSLDPCBP (750 x 750 Size)	Single Direction Right Curve Model: VATCS/Wa-3R/SD/L/DL/PT  Uniplan Part Number: WWWa-3RSLDPCAP (600 x 600 Size) WWWa-3RSLDPCBP (750 x 750 Size)	<b>Wa-3R</b>  <b>Curve</b>
<b>Wa-4L</b>  <b>Sharp Reverse Curve</b>	Single Direction Left Curve Model: VATCS/Wa-4L/SD/L/DL/PT  Uniplan Part Number: WWWa-4L-SLDPCAP (600 x 600 Size) WWWa-4L-SLDPCBP (750 x 750 Size)	Dual Direction Curve Model: VATCS/Wa-4LR/SD/L/DL/PT  Uniplan Part Number: WWWa-4LRSLDPCAP (600 x 600 Size) WWWa-4LRSLDPCBP (750 x 750 Size)	Single Direction Right Curve Model: VATCS/Wa-4R/SD/L/DL/PT  Uniplan Part Number: WWWa-4RSLDPCAP (600 x 600 Size) WWWa-4RSLDPCBP (750 x 750 Size)	<b>Wa-4R</b>  <b>Sharp Reverse Curve</b>
<b>Wa-5L</b>  <b>Reverse Curve</b>	Single Direction Left Curve Model: VATCS/Wa-5L/SD/L/DL/PT  Uniplan Part Number: WWWa-5L-SLDPCAP (600 x 600 Size) WWWa-5L-SLDPCBP (750 x 750 Size)	Dual Direction Curve Model: VATCS/Wa-5LR/SD/L/DL/PT  Uniplan Part Number: WWWa-5LRSLDPCAP (600 x 600 Size) WWWa-5LRSLDPCBP (750 x 750 Size)	Single Direction Right Curve Model: VATCS/Wa-5R/SD/L/DL/PT  Uniplan Part Number: WWWa-5RSLDPCAP (600 x 600 Size) WWWa-5RSLDPCBP (750 x 750 Size)	<b>Wa-5R</b>  <b>Reverse Curve</b>
<b>Wa-6L</b>  <b>Winding Road</b>	Single Direction Left Curve Model: VATCS/Wa-6L/SD/L/DL/PT  Uniplan Part Number: WWWa-6L-SLDPCAP (600 x 600 Size) WWWa-6L-SLDPCBP (750 x 750 Size)	Dual Direction Curve Model: VATCS/Wa-6LR/SD/L/DL/PT  Uniplan Part Number: WWWa-6LRSLDPCAP (600 x 600 Size) WWWa-6LRSLDPCBP (750 x 750 Size)	Single Direction Right Curve Model: VATCS/Wa-6R/SD/L/DL/PT  Uniplan Part Number: WWWa-6RSLDPCAP (600 x 600 Size) WWWa-6RSLDPCBP (750 x 750 Size)	<b>Wa-6R</b>  <b>Winding Road</b>

### Unipart Dorman

173 Main Street, Bath,  
Ontario, K0H 1G0, Canada

Tel: +1 613 352 3458

Fax: +1 613 352 6845

email: [dorman.enquiries@unipartdorman.com](mailto:dorman.enquiries@unipartdorman.com)

[www.unipartdorman.com](http://www.unipartdorman.com)



Visit [www.uniparttrail.com](http://www.uniparttrail.com) for details  
of our Worldwide Regional Offices